

40000 series Universal DVR

Specifications (EX-SDI, HD-SDI, 960H)

Class				Blue			
Video	Input					16 BNC	
	Input Resolution	2MP, 960H					
	Output	1 HDMI , 1 VGA , 1 RCA SD					
	Output Resolution	FHD, SXGA, XGA					
Recording	Speed	30fps/ch(2MP)					
	Resolution	2MP, 960H					
Audio	Input	4 RCA					
	Output	1 HDMI, 1 RCA					
Interface	Senser In / Out		4 / 1 - NC / NO				
	USB	2 x USB 2.0					
	PTZ / Keyboard	2 x RS485 - Terminal Block					
	ATM /POS	Ethernet POS					
Network	Interface	Ethernet 10/100/1G					
	Compression	H.264. JPEG					
	Speed	20fps(2MP)					
	Resolution	Max. 2MP					
Storage	Primary / External					2 HDD, 1 eSATA	
System	OS	Embedded Linux (Built-in Flash Memory)					
	Pre / Post-Alarm	5sec /5sec~5min					
	Recording Mode	Continuous, Event, Schedule					
	Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time					
	Backup Interface	USB, Network					
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data					
	Alarm Action	Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push					
	User	15 Users (Admin, User1 ~ User14)					
	Network Viewer	Netus, VMS, Web Viewer, Mac Viewer, SmartEyes_Pro(iOS, Android)					
General	Size					340 x 59 x 300 mm	
	Weight(w/o HDD)					4kg	
	Temp / Humidity	5 ~ 40°C /10% ~80%					
	Power Supply	AC 120,50/60 Hz		12V / 5A			
	Power Consumption			60 Watts			

Specifications is subject to change without advanced notice.