

# 50000 series-7brid

## Specifications (EX-SDI, HD-SDI, TVI, AHD, CVI, 960H, IP)

Class		Blue	
Video	Input		16 BNC 1-4 IP
	Input Resolution	4MP, 3MP, 2MP, 960H	
	Output	1 HDMI , 1 VGA , 2 BNC ( 1 HD , 1 SD)	
	Output Resolution	FHD, SXGA, XGA	
Recording	Speed	15fps/ch(4MP), 30fps/ch(2MP)	
	Resolution	4MP, 3MP, 2MP, 960H	
Audio	Input	4RCA	
	Output	1 HDMI, 1 RCA	
Interface	Senser In / Out		4 / 1 - NC / NO
	USB	2 x USB 2.0	
	PTZ / Keyboard	2 x RS485 - Terminal Block	
	ATM /POS	Ethernet POS	
Network	Interface	2 x Ethernet 10/100/1G	
	Compression	H.264. JPEG	
	Speed	10fps(4MP), 20fps(2MP)	
	Resolution	Max. 4MP	
Storage	Primary / Enternal		3 HDD, 1 eSATA
System	OS	Embedded Linux (Built-in Flash Memory)	
	Pre / Post-Alarm	5sec /5sec~5min	
	Recording Mode	Continuous, Event, Schedule	
	Data Search	Smart, Panorama, Calendar, Multi Day / Time, Event, Go to Time	
	Backup Interface	USB, Network	
	Backup Type	Video(RMS, AVI), Capture(JPEG), Log List, Setup Data	
	Alarm Action	Buzzer, PIZ Preset, E-mail, Relay, Spot, Event Popup, Callback, FTP, Push	
	User	15 Users (Admin, User1 ~ User14)	
	Network Viewer	Netus, VMS, Web Viewer, Mac Viewer, SmartEyes_Pro(iOS, Android)	
	ONVIF	ONVIF Profile S	
General	Size		430 x 88 x 270 mm
	Weight(w/o HDD)		4kg
	Temp / Humidity	5 ~ 40°C /10% ~80%	
	Power Supply	AC 120,50/60 Hz	12V / 5A
	Power Consumption		60 Watts

*\*\*Specifications is subject to change without advanced notice.\*\**