


Specifications EZdvr-NVR 16ch)

Line Up		HD-IP(NVR)	
Series		Lite	
Image			
Model Name			
System	OS	Embedded Linux	
	Language	Chinese, Chinese(S), Dutch, English, French, German, Hebrew, Hungari, Italian, Japanese, Korean, Latvian, Persian, Polish, Portuguese, Russian, Spanish, Sweden, Turkish, Arabic	
	Time Accuracy	5ppm (12.5sec/month)	
	Time Sync.	NTP, GMT, DST	
Camera	User	4 Users (Admin, installer, dm, manager)	
	IP Camera	ONVIF	
Video	IPC Input	16c	
	Display Rate	Max. UHD	
	Output Interface	HDMI,	
Audio	Spot	no spot - need separate video server	
	Input Interface	no onboard POE	
	Output Interface	RCA	
	Compression	H.264, H265	
Video Recording	Speed	Max.30fps/ch	
	Resolution	2MP & 4MP	
	Mode	Schedule	
	Event	Motion, Local Sensor	
Audio Recording	Bit Rate	Max. 8Mbps/ch	
	Compression	G.711u	
Playback	Search	Go to first rec. time, Go to last rec. time,Go to last search time,Calenda, Log viewer, Smart search,Multi-time & day search, Event search	
	Mode	Event only playback, Backward, Pause, Frame by frame, Speed up (x1 ~ x32, x300)	
Network	Interface	RJ45 (Ethernet 10/100/1G) x 2	
	Compression	H.264	
	Speed	Max. 2MP 15fps/ch	
	Resolution	Max. 2MP(1080p)	

Backup	Interface	USB2.0, Network							
	Format	Video clip (Backup viewer), JPEG Still ImageLog list, Setup data							
Alarm	Post-Alarm	5sec~5min							
	Motion Grid	22 x15							
	Alarm Action	E-mail, Event Popup, Buzzer, Relay,PTZ Preset,Remote CMS, Front LED							
	Input / Output	4/1							
Display	HDMI	4K, FHD, SxGA, XGA							
	VGA	Full HD, SxGA, XGA							
	TV								
	Mode	16/9/4/1/SEQ/BIG - LIVE, 16/9/4/1 - P.B							
External Interface	PTZ / Keyboard	2 RS485 - Terminal Block							
	ATM/POS	RS232C - Terminal Block, Ethernet POS							
Storage	Primary	6TB (16ch)							
	External	N/A N/A							
Features	POE				N/A				
	Jog-shuttle								
	RTSP								
	Capture	Yes							
Electrical	Input Voltage (DVR)	DC 12V, 5A							
	Input Voltage (PoE)	N/A							
	Camera Power Output	IEEE802.3af							
General	Power Supply	12V/5A - Level 6							
	Consumption			60W		60 Watts, 96 Watts(PSE)			
	Operating Temp.	5 ~ 40 °C							
	Humidity	10 ~ 80%							
	Weight w/o HDD	3Kg							
	Dimension	340 x 59 x 300 mm							
	Certification	CE, FCC, RoHS Compliance							

Confidential